

# ZEBRA 12

Rough Terrain 4x4 articulating boom lift



**ATN**<sup>®</sup>

[www.atnpiaf.com](http://www.atnpiaf.com)



On-board diagnostic screen



4 wheel drive

# ZEBRA 12

## ADVANTAGES

- Outstanding horizontal reach.
- High ground clearance.
- High drive speed.
- Proportional intuitive drive and lift controls.
- Easy to maintain (on-board diagnostic screen system).
- Designed and manufactured for heavy-duty use.

ZEBRA 12	
Working height	12,20 m (40 ft. 0,3 in.)
Platform height	10,20 m (33 ft. 5,5 in.)
Horizontal reach	8,50 m (27 ft. 10,6 in.)
Up and over clearance	4,42 m (14 ft. 6 in.)
Lift capacity	230 kg (507 lbs.)
Turntable rotation	2 x 178°
Platform rotation	2 x 90°
Turntable tailswing	zero
Jib rotation	133°
<b>A</b> Platform width	1,45 m (4 ft. 9 in.)
<b>B</b> Platform length	0,80 m (2 ft. 7,5 in.)
<b>C</b> Width	1,94 m (6 ft. 4,4 in.)
<b>D</b> Length - stowed	6,05 m (19 ft. 10 in.)
<b>E</b> Height - stowed	2,11 m (6 ft. 11 in.)
<b>F</b> Length - storage	4,50 m (14 ft. 9 in.)
<b>G</b> Height - storage	2,68 m (8 ft. 9,5 in.)
<b>H</b> Wheelbase	2,00 m (6 ft. 6,7 in.)
<b>I</b> Ground clearance centre	0,39 m (1 ft. 3 in.)
Turning radius - inside	1,57 m (5 ft. 1,8 in.)
Turning radius - outside	4,00 m (13 ft. 1,5 in.)
Tyres	LSW305-546

Drive speed - stowed	6 km/h (3,73 mph)
Drive speed - raised	1 km/h (0,62 mph)
Gradeability *	45%
Tilt value	4°
Weight	5150 kg (11,354 lbs)
Max.ground bearing pressure	3 kg / cm <sup>2</sup> (43 psi / in. <sup>2</sup> )

Diesel engine	KUBOTA D1105 19 kW
Fuel tank capacity	54 L (14,3 gal.)
Hydraulic tank capacity	60 L (15,8 gal.)
Auxiliary power unit	12V DC

\* See operator's manual for details regarding slope ratings.

## STANDARD FEATURES

- Overload sensor.
- Lifting facilities.
- On-board fuel tank indicator on the platform.
- On-board LCD colour diagnostic screen system.
- Rough terrain special tyres.

## OPTIONS

- GPS location mapping and telematics control system.
- Oscillating axle.
- 220V AC power to platform.
- Air line to platform.
- Special paint colour(s).



This product complies with European regulations in force(EN 280).  
Due to our constant improvement policy,  
ATN reserves the right to make any modifications  
without any prior notice.

